

BUTINOX Interiør Heftgrunn

Product description

Type

A waterborne, matt acrylic primer.

Features and benefits

It has low odour. Has good flow and minimal sagging. Good adhesion to the surface. Can be painted with acrylic and alkyd paint.

Recommended use

Used as primer on interior surfaces such as panels, doors, windows, trimmings, furnishings, vinyl wallpaper and other wall coverings, boards, hard boards and tiles in dry rooms. Can be used as first coat on particle board with waxed surface and vinyl.

The product should not be used on wall filler/joint filler.

Product data

Packaging size	0.75 L (BASE 0.68 L), 3 L (BASE 2.7 L) and 10 L (BASE 9 L)
Base availability	Tilnærmet A-base.
Tinting	The product can be tinted according to A-base recipes to approximately colour over Butinox Colour Manager.
Colors	A-base may be used untinted as White.
Gloss level	Matt 05
Solids by volume	35 ± 2 volume%
Specific gravity	1.4
VOC for Ready-for-Use Mixture	EU limit value for the product (cat. A/g): 30 g/l. The product contains max 15 g/l VOC.

Application data

Remarks

Contents of tins with different production numbers should be mixed to avoid possible colour deviations. Stir well before use.

Perform a test application on tiles to check adhesion.

Application equipment / methods

Brush, roller or spray.

Cleaning of painting tools

Clean with water and soap.

Spreading rate and film thickness

	Spreading rate per coat (m ² /liter)	Film thickness per coat (µm)	
		Wet (calculated)	Dry (calculated)
Recommended:	8 - 10	100 - 125	35 - 44

Thinner

Shall not be thinned.

Conditions during application

Temperature of air and substrate must be above +10 °C during painting.

Drying times

Drying times deviate because of changes in temperature, air humidity, air circulation and film thickness.

The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	23 °C
Substrate temperature	23 °C

Dust dry	1 h
Recoatable, minimum	2 h

Directions for use

Surface preparation

The substrate must be clean, sound and dry. The surfaces are washed with **BUTINOX Interiørvask** or **TRESTJERNER Gulvrens** and sanded with grinding paper.

Pretreatment

Knots are insulated with **JOTUN Kvistlakk vanntynnet** or with **BUTINOX Interiør Sperrende Maling**.

Primer

BUTINOX Interiør Heftgrunn: 1 coat.

Maintenance

Please refer to the FDV datasheet for information regarding maintenance and repair of the painted surface.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste

Liquid paint must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Must be empty and dry

Environmental labelling



The product is recognized by Miljømerking Norge, and conforms with the demands of the environmental label Svanen (the swan).

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

NOBB number

This document covers the following NOBB numbers:

45492175, 45492186, 45492372

Contact information

Scanox AS
P.O.Box 904 Brakerøya
3002 Drammen
Norway

Tel: +47 32 24 43 00
Fax: +47 32 84 13 85
SDSscanox@scanox.no

Disclaimer

The information in this document is given to the best of Scanox' knowledge, based on laboratory testing and practical experience. Scanox' products are considered as semi-finished goods and as such, products are often used under conditions beyond Scanox' control. Scanox cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Scanox reserves the right to change the given data without further notice.

Users should always consult Scanox for specific guidance on the general suitability of this product for their needs and specific application practices.

Technical Data Sheet

BUTINOX Interiør Heftgrunn



If there is any inconsistency between different language issues of this document, the Norwegian (Norway) version will prevail.