

TYRILIN Panelrens

Product description

Type

TYRILIN Panelrens is a specially powerful formulated cleaner for yellowed panel. The product is a concentrate to be diluted with water (1:10).

Features and benefits

c removes dirt, lignin and fat from yellowed woodwork in an efficient manner.

On yellowed panel, the cleaner alone will illuminate the panel and provide the best basis for further processing. Resin is removed from the surface of new woodwork, and you get a better, smoother penetration of surface treatment. This allows interior stains to penetrate into the woodwork which gives a homogenous, nice appearance.

The product is highly degreasing and suitable for cleaning of very contaminated areas. Wear protective gloves and eye protection.

Tyrilin Panelrens has a fresh scent and is slightly perfumed.

Recommended use

TYRILIN Panelrens is to be used for the cleaning of new and yellowed panel prior to application of stain and other transparent products indoors, as well as for the cleaning of previously treated surfaces before new treatment. The product is intended for yellowed spruce and pine panel. Can also be used for new woodwork. for best result.

TYRILIN Panelrens can also be used to degrease oily woods like oak and teak. Please note that oak and other hardwoods may become discolored. Perform a test cleaning.

Product data

Packaging size	1 liter plastic bottle.
Specific gravity	1.01
pH value	10 Basic.
Contents	EDTA < 5 %. Nonionic surfactants < 5 %.
Ingredients	Ammonia solution 24 % Dodecylbenzene sulphonic acid Tetra sodium ethylenediamine tetraacetate Methyl Hydroxyethylcellulose Tridecyl Alcohol Ethoxylate

Application data

Application equipment / methods

Cloth, mop, sponge.

Recommended per liter of concentrate: – 100

Product mixing ratio (by volume)

1 liter to 10 liters water.

Conditions during application

Temperature of air and substrate must be above +10 °C when using the product.
It is recommended to wear gloves and goggles. Provide good ventilation.

Method of use

TYRILIN Panelrens is mixed with water in the ratio of 1 part **TYRILIN Panelrens** to 10 parts of water. Clean the woodwork with diluted detergent. Avoid using a stronger solution. Apply the mixture using a cloth. Then wipe the surface with a cloth slightly soaked with clean, lukewarm water.
Make sure the woodwork is dry before further processing and that residues of cleaning liquid are removed.

Storage

In storage and in transport keep the container frost free and upright.
Durability: 2 years in unopened bottle.

Disposal of waste

Detergent must not be discharged into drains, but to a reception centre for dangerous waste.



Must be empty and dry

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

NOBB number

This document covers the following NOBB numbers:

49558721

Contact information

Scanox AS
P.O.Box 904 Brakerøya
3002 Drammen
Norway

Tel: +47 32 24 43 00
Fax: +47 32 84 13 85
SDSscanox@scanox.no

Disclaimer

The information in this document is given to the best of Scanox' knowledge, based on laboratory testing and practical experience. Scanox' products are considered as semi-finished goods and as such, products are often used under conditions beyond Scanox' control. Scanox cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Scanox reserves the right to change the given data without further notice.

Users should always consult Scanox for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the Norwegian (Norway) version will prevail.