

## QUICK Bengalack Merkespray

### Product description

#### Type

**QUICK Bengalack Merkespray** is a fast-drying alkyd paint. It is available in white and fluorescent orange.

#### Features and benefits

**QUICK Bengalack Merkespray** is used for marking on most surfaces; also moist.

#### Recommended use

**QUICK Bengalack Merkespray** has good adhesion to substrates such as asphalt, concrete, stone, gravel, wood, grass and snow.

### Product data

<b>Packaging size</b>	Spray can (net content about 500 ml).
<b>Colors</b>	White and fluorescent orange.
<b>Gloss level</b>	Silky matt
<b>Generic type</b>	Alkyd.
<b>Flash point</b>	-7 °C
<b>VOC for Ready-for-Use Mixture</b>	EU limit value for the product (cat. B/e): 840 g/l. The product contains max 840 g/l VOC.

### Application data

#### Remarks

Propellant: Butane/Propane.  
The product is classified as extremely flammable.

#### Application equipment / methods

Shake vigorously for 2 min. before use. Apply evenly in the desired film thickness.

To be used in the up / down position on the desired surface. Spray evenly and thinly at a distance of approx. 30 cm. Keep the can in motion during application.

After use, turn the can and spray until it only comes with propellant gas.

#### Cleaning of painting tools

White Spirit

## Drying times

The drying time is affected by temperature, air humidity and film thickness.

### The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	23 °C
Substrate temperature	23 °C

Recoatable, minimum	Ca 5 min.
Dry to use / careful use	Min. 1 hour
Excessive loads / fully cured	3–4 weeks

## Storage

In storage and in transport keep the container upright. Can be stored in freezing temperatures.

## Disposal of waste

Empty containers and residues of contents are delivered to municipal waste disposal or nearest environmental station.



## Environmental labelling

**BREEAM® NOR** The product meets the requirements of the BREEAM-NOR for the VOC and the A20 list.

## Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

**First-aid measures**, refer to section 4.

**Handling and storage**, refer to section 7.

**Transport information**, refer to section 14.

**Regulatory information**, refer to section 15.

## Miscellaneous

### NOBB number

This document covers the following NOBB numbers:

55805256, 55805260

### NOBB module number

42168633

### Contact information

Scanox AS  
P.O.Box 904 Brakerøya  
3002 Drammen  
Norway  
Tel: +47 32 24 43 00

### Disclaimer

The information in this document is given to the best of Scanox' knowledge, based on laboratory testing and practical experience. Scanox' products are considered as semi-finished goods and as such, products are often used under conditions beyond Scanox' control. Scanox cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Scanox reserves the right to change the given data without further notice.

Users should always consult Scanox for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the Norwegian (Norway) version will prevail.