

BUTINOX Husvask og Kraftvask

Product description

Type

Phosphate-free, alkaline and biodegradable detergent.

Features and benefits

Husvask and Kraftvask in one and the same product. Effective against all types of dirt such as grease, oil, soot, soil, moss, and the like. May appear corrosive to glass and aluminum mixed as Kraftvask. Does not damage grass or plants if rinsed quickly. Be careful not to get the detergent on self cleaning windows as it may damage the cleaning layer of the glass.

Recommended use

As Husvask: Used outdoors as an annual cleaning of painted / stained surfaces as well as decking, outdoor areas and outdoor furniture etc.

As Kraftvask: Used outdoors for cleaning of previously treated surfaces to be stained or painted. Well suited to the cleaning of fouled roof tiles and other highly fouled surfaces. Well suited as coarse wash the courtyards, garages and workshops.

Product data

pH value	>12
Contents	Contains: < 5% non-ionic surfactants
Ingredients	2-(2-butoxyethoxy)ethanol Disodium Ethoxylated alcohols, C16-18 Tetrasodium N,N-bis(carboxylatomethyl)-L-glutamate sodium hydroxide Quartenair C11-C14 alkylaminethoxylate, salt

Application data

Application equipment / methods

Apply with low-pressure sprayer or pressure washer with soap dispensing equipment.

Pressure washer must be used with caution.

The distance between nozzle and surface: Min. 30 cm.

At pressures above 70 bar: The distance to the wall/substrate and the spray angle must be increased further. Intense stream or the use of "turbo nozzle" could destroy cladding surface in total, and should therefore be avoided.

When using high pressure washers with soap application equipment, make sure that your equipment applies the soap mixture with the correct mixing ratio. If in doubt, use low-pressure spray.

After the use of airless spray., pump clean water through the injector.

For your own safety, avoid inhalation of spray mist, use skin and eye protection.

Method of use

Method of use as Husvask and annual outdoor maintenance wash

Thinning:	1 part BUTINOX Husvask og Kraftvask to 20 parts water. Well suited for annual house washing, terrace washing and for other outdoor surfaces, except for cars, boats and caravans.
Application:	Apply with low-pressure sprayer or pressure washer with soap dispensing equipment. Well suited as foam wash. On vertical surfaces the detergent should be applied from the bottom upwards. Allow the solution to work for at least 2-5 minutes. Avoid working in direct sunlight. The soap mixture should not dry on the surface. Rinse thoroughly with water. On vertical surfaces, start flushing from below.
Finishing treatment:	Fouled surfaces should be disinfected with BUTINOX Sopp- og Algefjerner .

Method of use as Kraftvask

Thinning:	1 part BUTINOX Husvask og Kraftvask to 10 parts water. Well suited as washing before staining or painting as well as other outdoor surfaces that are muddy and fouled.
Application:	Apply with low-pressure sprayer or pressure washer with soap dispensing equipment. Well suited as foam wash. On vertical surfaces the detergent should be applied from the bottom upwards. Allow the solution to work for at least 2-5 minutes. Avoid working in direct sunlight. The soap mixture should not dry on the surface. Best and cleanest result is obtained in combination with brushes mounted on the extension stick. Rinse thoroughly with water. On vertical surfaces, start flushing from below.
Finishing treatment:	Fouled surfaces should be disinfected with BUTINOX Sopp- og Algefjerner .
Remarks:	On very muddy substrates the mixture can be 1: 5 and can then have a mattifying effect on painted surfaces / substrates. Then take extra precautions by protecting yourself and surrounding areas.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste

Empty containers and residues of contents are delivered to municipal waste disposal or nearest environmental station.



Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued. Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

NOBB number

This document covers the following NOBB numbers:

56112537, 56112541

NOBB module number

22531115

Contact information

Scanox AS
P.O.Box 904 Brakerøya
3002 Drammen
Norway
Tel: +47 32 24 43 00

Disclaimer

The information in this document is given to the best of Scanox' knowledge, based on laboratory testing and practical experience. Scanox' products are considered as semi-finished goods and as such, products are often used under conditions beyond Scanox' control. Scanox cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Scanox reserves the right to change the given data without further notice.

Users should always consult Scanox for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the Norwegian (Norway) version will prevail.