

SCANOX Grovsparkel

Product description

Type

SCANOX Grovsparkel is a lightweight hand putty compound with added fillers.

Features and benefits

The filler has particularly good filling properties, is smooth and has good adhesion.

Recommended use

SCANOX Grovsparkel has effective filling properties and is a repair filler for damages to the substrate, unevenness and for damages to concrete, plaster and building boards. It can be used for full treatment on concrete and for filling of rough substrates. The filler shall not be used in connection with joint filling on gypsum boards joints.

Product data

Packaging size	10 liter
Solids by volume	70 ± 2 volume%
Particle size	0 -0.3 mm
Filling properties	0-10 mm mm
pH value	8 to 9

Application data

Application equipment / methods

The filler is ready for use and applied with a wide trowel.

Cleaning of painting tools

Water.

Recommended spreading rate

Depending on the substrate.

Thinner

Should normally not be thinned.

Drying times

Depending on film thickness, substrate type, temperature, humidity, ventilation.
Low temperature and high humidity prolongs the drying time considerably.

The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	23 °C
Substrate temperature	23 °C

Dust dry	2–4 hours
Recoatable, minimum	24 hours

Directions for use

Substrate	Treatment
Old surfaces with wounds and unevenness in wall and ceiling:	Old surfaces are washed with BUTINOX Interiørvask and sanded. Remove concrete bumps and unevennesses. Application and smoothing for the filler should be done with a spatula. Fillings up to 10 mm can be done in one treatment without cracking. Use sandpaper or felt trowel for sanding of fillers.

Maintenance

Not applicable. The product is not used alone.

Management, Operation and Maintenance

Please refer to the FDV datasheet for information regarding maintenance and repair of the painted surface.

Storage

In storage and in transport keep the container frost free and upright.
Storage ca 12 months if unopened packaging.


Disposal of waste

Empty containers and residues of contents are delivered to municipal waste disposal or nearest environmental station.



Approvals

CE-marking



Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

NOBB number

This document covers the following NOBB numbers:

42935616

NOBB module number

22529127

Contact information

Scanox AS
P.O.Box 904 Brakerøya
3002 Drammen
Norway
Tel: +47 32 24 43 00

Disclaimer

The information in this document is given to the best of Scanox' knowledge, based on laboratory testing and practical experience. Scanox' products are considered as semi-finished goods and as such, products are often used under conditions beyond Scanox' control. Scanox cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Scanox reserves the right to change the given data without further notice.

Users should always consult Scanox for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the Norwegian (Norway) version will prevail.