

SCANOX Sparkel for Treverk

Product description

Type

Light acrylic filler.

Features and benefits

Dries quickly, is easy to sand and gives a very nice and hard surface.

Recommended use

For filling of doors, moldings, nail holes, tabletops, furniture, stairs and other woodwork to be painted.

Product data

Packaging size	0.4 L tube and 3 L pail.
Colors	White.
Generic type	Acrylic emulsion.
Solids by volume	59 ± 2 volume%
Specific gravity	1.8
Filling properties	0-1 mm
pH value	9 (at 10 % concentration)

Application data

Application equipment / methods

Steel trowel or filler knife bakelite.

Cleaning of painting tools

Water.

Product mixing ratio (by volume)

One-component.

Thinner

Should normally not be thinned.

Conditions during application

Temperature of substrate and air must be minimum +10 °C.

Drying times

Thick layers, low temperature, high humidity and low air circulation will prolong the drying time.

The drying time is measured by stated values:

Relative Humidity (RH)	50 %
Air temperature	23 °C
Substrate temperature	23 °C

Dust dry	30 min.
Surface (touch) dry	4 h
Recoatible, minimum	4 h
Dry to use / careful use	4 h

Directions for use

The surfaces must be clean before filling.

Grind away any protruding unevenness. Clean with **TRESTJERNER Gulvrens**. Glossy surfaces should be sanded.

New woodwork to be primed with **TRESTJERNER Sperregrunning**.

Apply the filler in holes, damages and roughness of the substrate. Do not apply more than necessary. Pull off excess with a filler spade.

To obtain best possible result, 2 layers of filler is required. Lightly sand excavated filler and remaining unevenness before applying 2nd treatment. Use sandpaper or felt trowel for sanding of fillers.

Large damages/scratches must be filled several times, until the surface is smooth when the filler is dry.

Maintenance

Not applicable. The product is not used alone.

Please refer to the FDV datasheet for information regarding maintenance and repair of the painted surface.

Storage

In storage and in transport keep the container frost free and upright.

Disposal of waste

Filler must not be emptied into drains or watercourses. It must be delivered to an approved local environmental protection station.



Must be empty and dry

Health and safety

Please observe the environmental and precautionary notices displayed on the container.

A Material Safety Data Sheet for the product has been issued.

Detailed information regarding health and safety risks and precautions for the use of this product is specified in the product's Safety Data Sheet.

First-aid measures, refer to section 4.

Handling and storage, refer to section 7.

Transport information, refer to section 14.

Regulatory information, refer to section 15.

Miscellaneous

NOBB number

This document covers the following NOBB numbers:

45611580, 42935620

Contact information

Scanox AS
P.O.Box 904 Brakerøya
3002 Drammen
Norway

Tel: +47 32 24 43 00
Fax: +47 32 84 13 85
SDSscanox@scanox.no

Disclaimer

The information in this document is given to the best of Scanox' knowledge, based on laboratory testing and practical experience. Scanox' products are considered as semi-finished goods and as such, products are often used under conditions beyond Scanox' control. Scanox cannot guarantee anything but the quality of the product itself. Minor product variations may be implemented in order to comply with local requirements. Scanox reserves the right to change the given data without further notice.

Users should always consult Scanox for specific guidance on the general suitability of this product for their needs and specific application practices.

If there is any inconsistency between different language issues of this document, the Norwegian (Norway) version will prevail.